

ADC-66

High or Low Temp Conveyor machine. The ultimate Choice Best performance of all listed 66" conveyors

Specifications:

- ◆ Dishwasher Type: Conveyor Type
- ◆ Phase: 3
- ◆ 244 Racks/Hr
- ◆ Dimensions: 73.25" x 86" x 34.5"
- ◆ Conveyor speed: 6.8 ft/min.
- ◆ Interior Clearance: 19.25"
- ◆ Motor ratings: 1.5 HP scrap, 3 HP wash, 1/3 HP rinse, 1/3 HP conveyor



Energy Details:

- ◆ 90 amps
- ◆ 60 Hz
- ◆ Conveyor/Rinse Horsepower: 1/3 HP
- ◆ Wash Horsepower: 3 HP
- ◆ Voltage: 208 -240
- ◆ Incoming water temperature: 120°F (Low Temp) or 180°F (High Temp)
- ◆ Rinse Temperature: High Temp or Low Temp available
- ◆ Rinse Tank Usage: 2.3 kW
- ◆ Wash Tank Usage 18 kW
- ◆ Heater ratings: 18kW wash, 2.25kW

Water Consumption Details:

- ◆ Uses only .53gal/rack
- ◆ Total gallons per hour: 120 gal/hr
- ◆ Water inlet: 0.75" diameter

Features:

- ◆ Pre-wash scrap basket
- ◆ Overflow scraping feature
- ◆ Patented water control
- ◆ Auto-fill, auto-start, and shut-off features
- ◆ Water curtain activates prior to final rinse and initiates the rinsing process and acts as a shield
- ◆ Drain pump filter is a 2-stage pump strainer that eliminates wash pump obstructions and clogged jets; functions as a drain stopper
- ◆ Captive end caps allow for quick cleaning of spray arms
- ◆ Dual Fail Safe Heater Control allows for precise water control mechanism and only allows heaters to operate when tank is full.
- ◆ Fail-safe conveyor system eliminated damaged racks and has a slip clutch design to stop rack movement.

